

PRODUCT DESCRIPTION	TTSG02 silver metallic total transfer tamper evident tape designed to provide a message “VOID” reveals on lift tape and transferred onto the applied surface at when removal is attempted. The lift tape can’t be stuck back again, and the permanent destroy can’t be returned as initial. It shows obvious evidence of any unauthorized opening and deters stolen and manipulation continued.
----------------------------	--

		Typical Value	Unit	Test Method
FILM – PET	Thickness	60	Micron	ASTM D 3652
ADHESIVE	Thickness	27	Micron	ASTM D 3652
Adhesion from: Stainless Steel Glass Polypropylene Acrylic	THIS PRODUCT SHOWS TAMPERING WHEN REMOVAL IS ATTEMPTED BY LEAVING A VOID PATTERN ON THE APPLICATION SURFACE	N / 25mm	FTM 1 (72 hour dwell)	
Shear	2	Hours	FTM 8 (1 hour dwell on stainless steel with a 2kg weight)	
Probe Tack	420	gram/sq cm	ASTM D 2979	
LINER	Thickness	81	Micron	ASTM D 3652
COMPLETE CONSTRUCTION	Service Temp	-40 to 150	°C	
Application Temp	10	°C		

Converting Recommendations

Suitable for conventional and thermal transfer printing with wax, combo en resin ribbons.

Storage Recommendations

Material is stable for two years stored at max 21 °C and 50% relative humidity. Damp conditions, excessive heat and/or freezing conditions should be avoided.